

Classification: Physical Sciences, Physics

Slow slip is a mechanism for slow fronts in the rupture of frictional interfaces

J. K. Trømborg^a, H. A. Sveinsson^a, J. Scheibert^b, K. Thøgersen^a, D. S. Amundsen^c, A. Malthesørenssen^{a,1}

a. Department of Physics, University of Oslo, Oslo, NO 0316

b. Laboratoire de Tribologie et Dynamique des Systèmes, CNRS, Ecole Centrale de Lyon, Ecully, FR 69134

c. Astrophysics Group, University of Exeter, Exeter, GB EX4 4QL

1. malthes@fys.uio.no, +47 22856477

Keywords: friction, slow front, slow slip, multiscale modelling

The failure of the population of micro-junctions forming the frictional interface between two solids is central to fields ranging from biomechanics to seismology. This failure is mediated by the propagation along the interface of various types of rupture fronts, covering a wide range of velocities. Among them are so-called slow fronts, which are recently discovered fronts much slower than the materials' sound speeds. Despite intense modelling activity, the mechanisms underlying slow fronts remain elusive. Here, we introduce a multi-scale model capable of reproducing both slow fronts and the short-time slip dynamics observed in recent experiments. We identify slow slip as a phenomenon sufficient for allowing slow fronts to exist and responsible for selecting their velocity. Whether slow fronts are actually observed is not only controlled by the stresses but also by a microscopic state related to the local distribution of forces among micro-junctions. Our results show that slow fronts are qualitatively different from faster fronts. Since slow fronts are potentially as generic as slow slip, we anticipate that they might occur in the wide range of systems in which slow slip has been reported, including seismic faults.

Significance statement

Relative motion between solids in frictional contact is known to start progressively, with a slipping zone growing along the interface. The propagation of the front separating the stuck and slipping zones is usually very fast, but it can also be very slow, a phenomenon not yet understood. Using a multi-scale model, we demonstrate how slow fronts are the direct consequence of slow slip motion at the interface, relating two phenomena considered as distinct up to now. This shows that slow fronts are qualitatively different from faster fronts. Since slow fronts result from slow slip, we expect that they can occur in the wide range of systems in which slow slip has been reported, from engineering to seismology.

Introduction

The rupture of frictional interfaces is a central mechanism in many processes including snow slab avalanches (1), human object grasping (2) and earthquake dynamics (3). The rupture occurs through the propagation of a crack-like micro-slip front – the rupture front – across the interface. This front represents the moving boundary between a stick region and a slipping region that coexist within the contact. In so-called partial-slip situations, fronts propagate quasi-statically at a pace controlled by the external loading, as studied in mechanical engineering for decades (4, 5). Recently, fast cameras enabled the observation of much faster fronts, which are classified into three types: supershear fronts faster than the material's shear wave speed c_s , sub-Rayleigh fronts propagating at velocities close to c_s and slow fronts much slower than c_s (6-10). Whereas the two first types have been predicted theoretically, the physical mechanisms underlying slow fronts remain elusive.

A better understanding of slow fronts appears as a significant step towards an improved assessment of how frictional motion begins. It is also expected to shed light on the important topic of slow earthquakes, which have been increasingly reported in the last decade (3). In this context, an intense theoretical and numerical activity arose to investigate the origins and properties of rupture fronts. Two different approaches have been explored.

On the one hand, two- or three-dimensional elastodynamic models have been used to relate the macroscopic loading conditions to the stress field along the contact interface (11-14). These local stresses were indeed shown experimentally to play a role in the selection of the front type (8). However, the models were based on simple friction laws, e.g. Coulomb friction (13) or velocity-weakening friction (14), and did not exhibit slow fronts. On the other hand, fronts much slower than the speed of sound were produced by one-dimensional friction models using improved local friction laws involving an intrinsic time-scale. A material-dependent time-scale was indeed shown experimentally to control the transition between a

fast and a slow regime for the slip motion triggered by the front passage (15). The friction law used in the models was either an effective state-and-rate law (16, 17) or the collective dynamics of formation and rupture of a statistical number of micro-junctions (18, 19). However, because one-dimensional models are unable to reproduce realistic stress distributions at the interface, they do not allow for quantitative comparison with experiments. Here we combine the key features of both approaches to propose a multi-scale model for rupture fronts. We demonstrate that the model simultaneously reproduces two separate, unexplained experimental observations: the transitions between fast and slow front propagation during single rupture events; and the transition from fast to slow slip motion at the interface shortly after rupture. In addition, through a more general study of the model, we show that slow slip is a sufficient phenomenon for slow fronts to arise, and we identify parameters involved in front type selection.

Model description

The frictional stability of a system made of two solids in contact depends on the level of normal and shear stresses at the contact interface. These interfacial stresses result from the external forces applied at the boundaries of the solids, transmitted through the bulk. Slip motion will in general be triggered when the local interfacial shear stress reaches a threshold, the level of which crucially depends on the interface behavior law at the microscale.

The net contact between two solids generically consists of a large number of stress bearing micro-junctions whose nature depends on the type of interface. For rough solids, each micro-junction corresponds to a micro-contact between antagonist asperities, whereas for smoother surfaces the junctions can be solidified patches of an adsorbate layer (20). The three physical aspects of the junction behavior that we consider to be essential are as follows. 1) A micro-junction in its pinned state can bear a shear force f_T , provided it remains smaller than a threshold f_{thres} . When f_{thres} is reached, a local fracture-like event occurs, and the junction enters

a slipping state. 2) In the slipping state, the micro-junction can let the interface slip, either through the micro-slipping of micro-asperities in contact or through the fluidization of an adsorbate layer. During slip, the micro-junction sustains some residual force f_{slip} smaller than f_{thres} . 3) Slipping micro-junctions have a certain probability to disappear or relax after some time. For example, a micro-contact disappears when an asperity moves away from its antagonist asperity. Another example is a consequence of the sudden release of energy when pinned junctions break. This energy will transiently heat the region around the micro-junction (15). The rise in temperature will, during the time necessary for the interface to cool down, significantly increase the rate of a thermally activated relaxation of the slipping micro-junction (20). The important point here is that all such processes lead to the shear force drop being distributed in time. This can give rise to a slow slip motion, as generically observed at frictional interfaces (15, 20-24). In order for the interface to continue bearing the forces applied to it, the micro-junctions that disappear or relax are replaced by new, pinned junctions bearing a small tangential force f_{new} .

The physical aspects described above have been modeled in a simple way using the following assumptions. We consider the rough frictional interface between a rigid track and a thin linear elastic slider of length L and height H (Fig.1A, Methods). The bulk elastodynamics of the slider are solved using a square lattice of blocks connected by internal springs (Fig.1B) (13, 25). The multi-contact nature of the interface is modeled through an array of N_s tangential springs representing individual micro-junctions, attached in parallel to each interfacial block (Fig.1C) (18-20). The individual spring behavior is as follows (Fig.1F). A spring pinned to the track stretches linearly elastically as the block moves, acting with a tangential force f_T on the block. When the force reaches the static friction threshold f_{thres} , the micro-junction ruptures

and the spring becomes a slipping spring acting with a dynamic friction force^{*} $f_T = f_{\text{slip}}$. After a random time t_R drawn from a distribution $T(t_R)$, the slipping spring disappears. It is replaced immediately by a pinned, unloaded spring ($f_{\text{new}}=0$) and a new cycle starts. Here we use $T(t_R)$ as a simplified way of modeling the distribution of times after which micro-junctions relax. Due to the variety and the complexity of the underlying processes, we did not try to derive $T(t_R)$ for a specific situation. Rather, we chose to model $T(t_R)$ in the simplest way, as a Gaussian with average time $\langle t_R \rangle$ and width δt_R (Methods). The shape of $T(t_R)$ is not crucial: we obtain qualitatively similar results with an exponential distribution. The width of $T(t_R)$ is the only source of randomness in our model and causes the interface springs of a block to evolve differently from each other.

The model reproduces rupture front observations

In this section we use the model to reproduce unexplained experimental observations made by Fineberg and collaborators in polymethylmethacrylate. We use the loading conditions and material constants of Rubinstein et al. (6), as done in (13). We then select the parameters of the friction law in order to reproduce both the complex space-time evolution of the front velocity reported in (6) and the time-dependent interfacial slip history reported in (15).

The slider is first submitted to normal load F_N only. Then, a slowly increasing tangential load F_T is applied on its left side, at height h above the interface (Supporting Methods). Macroscopically (Fig.1D), the slider is first loaded elastically, yielding high shear stresses in the vicinity of the loading point. These growing stresses eventually trigger the slip of a first block, the motion of which increases the force on its neighbors (Fig.1E) until they also start to slip, and so on. This mechanism can result in the propagation of a rupture front across the

^{*} Both f_{thres} and f_{slip} are taken to be proportional to the normal force p on the corresponding block (Methods). This assumption ascribes the pressure dependence of the forces on a block to the individual forces bore by a constant number N_s of springs, rather than to a pressure dependent number of springs per block.

interface. The first such events arrest before reaching the contact's leading edge and correspond to so-called precursors to sliding (13, 26-29). In the following, we will consider the interface-spanning events (Fig.2) that are responsible for the large force drops in Fig.1D. We measure the front propagation speed v_c as a function of position x along the interface (Fig.2C) by defining rupture at the block scale, when the fraction of pinned springs drops below a threshold value (Figs.2A,B).

Figure 2A shows an event starting as a fast front ($v_c \sim c_s/3$), then turning into a slow front ($v_c \sim c_s/100$) at $x \sim 0.4L$, before turning back into a fast front at $x \sim 0.6L$. This space-time development is in excellent agreement with the experiments from which the model parameters were taken (6). In particular, the locations of the transitions between fast and slow fronts, the duration of the slow front ($\sim 1\text{ms}$) and the velocity ratio between fast and slow fronts are all matching the experimental observations. We find other events that are fast across the whole interface (Fig.2B). We emphasize that such spatially heterogeneous dynamics arise spontaneously in our model. This success is presumably due to the two-dimensionality of the model, which allows it to reproduce interfacial stress heterogeneities arising from macroscopic sample geometry and external loading (13).

Figure 3C shows the slip experienced by an interfacial block during an event, the time-evolution of which exhibits two distinct regimes. A fast slip regime is followed by a roughly linear slow slip regime, in good agreement with the slip history reported in (15). Notably, both the ratios of slip distances and of slip velocities experienced in either regime are matching the experimental observations.

The simultaneous agreement found with two independent measurements – reproducing the fronts' spatio-temporal dynamics at the slider scale and the slip dynamics at the block scale – indicates that our model can provide insight into the set of experiments reported by Fineberg

and collaborators. Because the basic ingredients of the model represent general features of frictional interfaces, we expect the model to be applicable to a larger class of systems.

Relationship between slow slip and slow fronts in the model

From this section on we change the scope from reproducing particular experiments to performing a systematic study of the model. We begin by varying select model parameters to unravel the mechanisms underlying slow fronts.

Figure 3C (reference curve) shows the slip history of a block during an event with a slow front (Fig.3A); it has both fast and slow slip regimes. Slow slip occurs after front passage and originates from the following mechanism: For each spring leaving the slipping state after t_R the friction force on the block is reduced. As a result the block moves a small distance, driven by the forces from the neighboring blocks. Slow slip then results from the succession of such incremental block movements. The slow slip velocity v_{slowslip} is inversely proportional to the mean slipping time $\langle t_R \rangle$ of the springs (Fig.3C, inset).

The fast-slow-fast front in (A) becomes an arrested front (B) when we restart the simulation in the same state, but with slow slip turned off. We do this by setting $f_{\text{new}} = f_{\text{slip}}$ so that springs leaving the slipping state no longer relax or disappear, but instead return to the pinned state bearing the same force as during slip. The front in (B) arrests where the fast-to-slow transition used to take place. These results support the following scenario: Slow fronts are fronts that would arrest in the absence of slow slip, but are pushed further by the increasing loading due to slow slip behind the front tip.

To show that slow slip is a sufficient condition for slow fronts to be allowed, we consider the following simplified model. We leave the microscale dynamics out by replacing the ensemble of springs connecting each block to the track with *a single spring*: The spring breaks when reaching the force $N_s f_{\text{thres}}$, it slides with a force $N_s f_{\text{slip}}$ and it returns to the pinned state still

bearing the force $N_s f_{\text{slip}}$ when the block velocity vanishes. Slow slip is introduced directly as a small velocity applied to the spring attachment point (Supporting Methods). Slow fronts are indeed observed in this simplified model (Fig.S1), and disappear if slow slip is turned off.

To characterize the relationship between slow slip velocity and slow front velocity, we consider both the complete and simplified models and use interfaces prepared as follows (Supporting Methods). We choose the normal force profile $p(x)$ to be uniform in space and constant in time and the initial shear force profile $\tau(x)=\tau_0$ to be uniform in space except in a region used to initiate front propagation (Fig.S2). We vary different model parameters, keeping the front initiation region unchanged, and systematically measure the slow front velocity $v_{c,\text{slow}}$ as a function of v_{slowslip} (Fig.3D,inset). Suitable rescaling (Supporting Equations) of v_{slowslip} allows all points to collapse on a single straight line (Fig.3D). This collapse shows that $v_{c,\text{slow}}$ is proportional to v_{slowslip} , with the same conversion factor for both models. We conclude that even though v_{slowslip} depends on the interfacial dynamics the conversion factor does not; it mainly depends on the way stresses are transferred from the slowly slipping region to the rupture tip.

Selection of the front type in the model

We now turn to the question of front type selection. Ben-David et al. (8) showed that slow (fast) fronts correlate locally with small (high) shear to normal stress ratio τ/p just before the event. In equilibrium, τ is the sum of the spring forces f_T for each block. Due to the randomness in the slip times t_R the individual f_T will be different. As in previous works (20, 30) it is useful to define a distribution $\phi(f_T)$ of the forces in the springs attached to each block. ϕ is a dynamical quantity evolving with both the loading on and the motion of blocks. Note that in general ϕ will be different for every block.

We find that the width σ of the distribution is as important as the stress ratio for front type selection. To demonstrate this we take event II as a reference and modify it by changing σ for all blocks at $x > 0.3L$. To isolate the effect of σ from the effect of the stress ratio on front propagation we increase σ , but keep $\tau_o(x)$ unchanged. We do this by making each block's $\phi(f_T)$ a uniform distribution while keeping its average unchanged (Fig.S3). We then restart the simulation and observe that the front has changed from a fast-slow-fast one (Fig.4A) to a fast one across the whole interface (Fig.4B). The reason for this behavior is that increasing σ from Fig.4A to Fig.4B weakens the interface, which enables the fast rupture to reach the leading edge without becoming a slow front. The weakening can be understood from Fig.4C, which shows the effective static friction coefficient $\mu_s^{\text{eff}} = \tau_{\text{max}}/p$ of an interface block, with τ_{max} the maximum friction force on the block before it starts to slip. Small (large) σ correspond to large (small) τ_{max} (Fig.S4), i.e. a locally stronger (weaker) interface, consistent with the fact that data points corresponding to slow fronts cluster at low σ in Fig.4C.

Figures 4A and 4B indicate that, besides τ/p , σ is involved in front type selection. Using interfaces prepared as in Fig.3D, we systematically vary the values of τ_o and σ and observe which front type is selected (Fig.4D). Low τ_o and σ lead to fronts that arrest before spanning the whole interface. Large τ_o and σ yield fast fronts. Global events containing a slow part are found in a region of intermediate τ_o and σ . These results are found qualitatively robust not only against changes in sample geometry or energy stored in the nucleation region, but also against changes in the individual behavior of the interfacial springs (Fig.S5). We therefore expect the main features of Fig.4D to be widely relevant.

Discussion

Up to now, the term slow front has been used in the literature to name any front propagating at least one order of magnitude slower than the material's wave speeds. Our results allow for a

tentative definition of the slow fronts first observed in (6). They are fronts that would arrest in the absence of slow slip, but are pushed further by the increasing loading due to slow slip behind the front tip. Importantly, the motion results from the intrinsic creep-like dynamics of the interface and not from an external driving. A direct consequence is shown in Fig.5A, where the increase in tangential load is stopped during the propagation of the slow front of Fig.2. We observe that the slow front is not affected and propagates exactly like in the original event, which indicates that the front is truly dynamic. This contrasts with the behavior of the event shown in Fig.5B, where the loading is applied to the bottom-left-most block. Extremely slow fronts are then observed, similar to the ones reported in e.g. (17-19), which propagate over the time-scale of the interval between two dynamic events. These fronts stop when the driving stops, indicating that they are of a different, quasi-static nature.

Our results make a direct bridge between the separate observations of slow fronts and slow slip in recent experiments (6, 15). As slow slip is observed in many systems from geoscience (3, 23, 24) to materials science (15, 21), we expect slow fronts to be possible in these systems too. The physical process underlying slow slip, *e.g.* thermal softening in glassy polymers (15), thermal creep in paper (21) and dilatant strengthening in subduction zones (22) differs from system to system. The present model does not aim at modeling one particular process. Rather, through the time distribution $T(t_R)$, we introduce the minimal generic ingredient necessary to yield a slow interfacial slip motion.

It was recently suggested that slow fronts are an intrinsic property of steady state friction laws with non-monotonic velocity dependence (16). However, in our model, the steady-state friction law that emerges from the micro-junction dynamics at the block scale is purely monotonic and decreasing (Fig.1G). Even if they share several properties, the question if both kinds of slow front are of the same nature is still open.

Using the simplified model, we demonstrated that slow fronts can in principle exist even if only one micro-junction is kept per block, i.e. the force distribution ϕ has width $\sigma=0$, provided slow slip is introduced in another way. However, we believe that virtually all frictional interfaces are of the multi-junction type at the relevant scale, e.g. micro-contact or molecular scale. Due to random physical properties or stochastic pinning/relaxation events combined with the previous sliding dynamics there will always be some disorder in the forces bore by the junctions, as recognized in various friction models (e.g. (18, 20, 30)). The disorder was shown to control e.g. the steady sliding friction force and the transition between smooth sliding and stick-slip regimes (30). Here we showed that the force distribution is also a key parameter in front type selection. It appears as a state parameter that, by controlling the effective friction threshold μ_s^{eff} at the block scale, is able to affect interfacial rupture in a way analogous to but different from the usual age state used in rate-and-state friction laws.

We believe that all our results are relevant to a large class of systems with a random population of stress-bearing entities having both a threshold like rupture behaviour and a time-dependent healing process, like in nanoscience (31), polymer science (32) and seismology (33).

Methods

Parameters are in Supporting Table S1. Spring j of block i has strength $f_{\text{thres}} = \mu_s p_i / N_s$ and stiffness $k_{ij} \propto \sqrt{p_i / N_s}$. The force on block i from spring j is $f_{Tij} = k_{ij}(x_{ij} - x_i)$, where x_{ij} is the attachment point of the spring to the track and x_i is the block's position. While slipping, the spring trails the block with x_{ij} adjusted in every time step to ensure $|f_{Tij}| \leq f_{\text{slip}} = \mu_d p_i / N_s$. If the block motion reverses, x_{ij} stops changing and remains fixed while $|f_{Tij}| \leq f_{\text{slip}}$. The probability distribution $T(t_R)$ is based on a Gaussian $T_G(t_R) = \frac{1}{\sqrt{2\pi}\delta t_R} \exp(-\frac{(t_R - \bar{t}_R)^2}{2\delta t_R^2})$, modified so that negative lifetimes are forbidden: $T(t_R) = T_G(t_R) + T_G(-t_R)$, $t_R \in [0, \infty]$. With the parameter values we use, $\langle t_R \rangle \cong \bar{t}_R$. In the simulations behind Fig. 3C and 3D, the ratio $\delta t_R / \bar{t}_R$ is maintained. Details on initialization and non-

frictional boundary conditions are in Supporting Methods. The motion is found using a Velocity Verlet scheme with $\Delta t = 2 \cdot 10^{-7}$ s.

References

1. Heierli J, Gumbsch P, Zaiser M (2008) Anticrack nucleation as triggering mechanism for snow slab avalanches. *Science* 321:240-243.
2. Johansson RS, Flanagan JR (2009) Coding and use of tactile signals from the fingertips in object manipulation tasks. *Nat. Rev. Neurosci.* 10:345-359.
3. Peng Z, Gombert J (2010) An integrated perspective of the continuum between earthquakes and slow-slip phenomena. *Nat. Geosci.* 3:599.
4. Johnson KL (1985) *Contact Mechanics* (Cambridge Univ. Press, Cambridge).
5. Prevost A, Scheibert J, Debrégeas G (2013) Probing the micromechanics of a multi-contact interface at the onset of frictional sliding. *Eur. Phys. J. E* 36:17.
6. Rubinstein S, Cohen G, Fineberg J (2004) Detachment fronts and the onset of dynamic friction. *Nature* 430:1005-1009.
7. Xia KW, Rosakis AJ, Kanamori H (2004) Laboratory earthquakes: the sub-Rayleigh-to-supershear rupture transition. *Science* 303:1859-1861.
8. Ben-David O, Cohen G, Fineberg J (2010) The dynamics of the onset of frictional slip. *Science* 330:211-214.
9. Nielsen S, Taddeucci J, Vinciguerra S (2010) Experimental observation of stick-slip instability fronts. *Geophys. J. Int.* 180:697-702.
10. Audry MC, Fretigny C, Chateauminois A, Teissere J, Barthel E (2012) Slip dynamics at a patterned rubber/glass interface during stick-slip motions. *Eur. Phys. J. E* 35:83.
11. Ben-Zion Y (2001) Dynamic ruptures in recent models of earthquake faults. *J. Mech. Phys. Solids* 49:2209-2244.
12. Di Bartolomeo M, Meziane A, Massi F, Baillet L, Fregolent A (2010) Dynamic rupture at a frictional interface between dissimilar materials with asperities. *Tribol. Int.* 43:1620-1630.

13. Trømborg J, Scheibert J, Amundsen DS, Thøgersen K, Malthe-Sørenssen A (2011) Transition from static to kinetic friction: Insights from a 2D model. *Phys. Rev. Lett.* 107:074301.
14. Kammer DS, Yastrebov VA, Spijker P, Molinari J-F (2012) On the propagation of slip fronts at frictional interfaces. *Tribol. Lett.* 48:27-32.
15. Ben-David O, Rubinstein S, Fineberg J (2010) Slip-stick and the evolution of frictional strength. *Nature* 463:76-79.
16. Bar Sinai Y, Brener EA, Bouchbinder E (2012) Slow rupture of frictional interfaces. *Geophys. Res. Lett.* 39:L03308.
17. Bouchbinder E, Brener EA, Barel I, Urbakh M (2011) Slow cracklike dynamics at the onset of frictional sliding. *Phys. Rev. Lett.* 107:235501.
18. Braun OM, Barel I, Urbakh M (2009) Dynamics of transition from static to kinetic friction. *Phys. Rev. Lett.* 103:194301.
19. Capozza R, Urbakh M (2012) Static friction and the dynamics of interfacial rupture. *Phys. Rev. B* 86:085430.
20. Persson BNJ (1995) Theory of friction: Stress domains, relaxation, and creep. *Phys. Rev. B* 51:13568-13585.
21. Heslot F, Baumberger T, Perrin B, Caroli B, Caroli C (1994) Creep, stick-slip, and dry-friction dynamics: Experiments and a heuristic model. *Phys. Rev. E* 49:4973-4988.
22. Segall P, Rubin AM, Bradley AM, Rice JR (2010) Dilatant strengthening as a mechanism for slow slip events. *J. Geophys. Res.* 115:B12305.
23. Ohnaka M, Kuwahara Y (1990) Characteristic features of local breakdown near a crack-tip in the transition zone from nucleation to unstable rupture during stick-slip shear failure. *Tectonophysics* 175:197-220.

24. Hirose H, Obara K (2005) Repeating short-and long-term slow slip events with deep tremor activity around the Bungo channel region, southwest Japan. *Earth Planets Space* 57:961-972.
25. Yim H, Sohn Y (2000) Numerical simulation and visualization of elastic waves using mass-spring lattice model. *IEEE T. Ultrason. Ferr.* 47:549-558.
26. Rubinstein S, Cohen G, Fineberg J (2007) Dynamics of precursors to frictional sliding. *Phys. Rev. Lett.* 98:226103.
27. Scheibert J, Dysthe DK (2010) Role of friction-induced torque in stick-slip motion. *EPL* 92:54001.
28. Maegawa S, Suzuki A, Nakano K (2010) Precursors of global slip in a longitudinal line contact under non-uniform normal loading. *Tribol. Lett.* 38:313.
29. Amundsen DS, Scheibert J, Thøgersen K, Trømborg J, Malthe-Sørensen A (2012) 1D model of precursors to frictional stick-slip motion allowing for robust comparison with experiments. *Tribol. Lett.* 45:357-369.
30. Braun OM, Peyrard M (2010) Master equation approach to friction at the mesoscale. *Phys. Rev. E* 82:036117.
31. Li Q, Tullis TE, Goldsby D, Carpick RW (2011) Frictional ageing from interfacial bonding and the origins of rate and state friction. *Nature* 480:233-236.
32. Cordier P, Tournilhac F, Soulié-Ziakovic C, Leibler L (2008) Self-healing and thermoreversible rubber from supramolecular assembly. *Nature* 451:977-980.
33. McLaskey GC, Thomas AM, Glaser SD, Nadeau RM (2012) Fault healing promotes high-frequency earthquakes in laboratory experiments and on natural faults. *Nature* 491:101-104.




Figure 1: Sketch and behavior of the multi-scale model. **(A)** Slider and external loading conditions. **(B)** Spring-block network modeling elastodynamics. **(C)** Surface springs modeling friction on a block. **(D)** Macroscopic loading curve, the ratio F_T/F_N of driving shear force to total normal force. **(E)** Mesoscopic loading curve, the ratio τ/p of shear to normal stress on a block. **(F)** Microscopic friction model for the spring loading curve, the ratio f_T/f_N of friction to normal force for one spring ($f_N=p/N_s$). **(G)** Steady state friction force on a block vs sliding velocity.




Figure 2: Two contact-sized events. **(A)** A fast-slow-fast event (I in Fig.1D). Spatio-temporal plot of the fraction of pinned springs. **(B)** A fast only event (III in Fig.1D) shown as in **A**. **(C)** Rupture front speed v_c vs front location for both events. Block rupture is defined to occur when 70% of interface springs have broken (white dashed line in colorbar). Front speed is measured as the inverse slope of the rupture line (indicated by arrows in **A,B**) using the end-points in a five point wide moving stencil.




Figure 3: Slow rupture is governed by slow slip. (A,B) Event II restarted at 1.0571 s with driving speed $V=0$, shown as in Fig.2A. Slow slip is either active (A) or turned off (B). (C) Slip profiles for block at $x=0.34L$ under varying $\langle t_R \rangle$ (A uses the reference $\langle t_R \rangle$). The fast slip part is not affected. Inset: slow slip speed is inversely proportional to $\langle t_R \rangle$. Error bars: minimum and maximum values. Dots: mean. Line: linear fit to mean values, through origin. (D) Data-collapse of slow rupture speed vs $v_{\text{slowslip}} k_i l_0 / (\tau_{\text{thres}} - \tau_0)$ for full and simplified models and wide variations in input parameters (legend). k_i : block-interface stiffness, l_0 : characteristic length (Supporting Equations), $\tau_{\text{thres}} = N_s f_{\text{thres}}$. Inset: unscaled data.




Figure 4: Role of microscopic force distributions in rupture dynamics. **(A)** Event II shown as in Fig.2A. **(B)** Event II restarted at 1.054 s with wider $\phi(f_T)$ in the region $x > 0.25L$ (arrow) results in a fast-only event. **(C)** $\bar{\mu}_s^{\text{eff}} = (\frac{\tau_{\text{max}}}{p} - \frac{f_{\text{slip}}}{f_N}) / (\frac{f_{\text{thres}}}{f_N} - \frac{f_{\text{slip}}}{f_N})$ vs $\tilde{\sigma} = \sigma / (f_{\text{thres}} - f_{\text{slip}})$ for all blocks in events I (green) and II (red), and for prepared events (black) with homogeneous $\bar{\tau}_0 = (\frac{\tau_0}{p} - \frac{f_{\text{slip}}}{f_N}) / (\frac{f_{\text{thres}}}{f_N} - \frac{f_{\text{slip}}}{f_N})$. $\bullet$ slow front, $\times$ fast front, and $\circ$ loading zone ($x < 2\text{cm}$). Solid (dashed) line is for uniform (bell-shaped) $\phi(f_T)$ (Fig. S4). **(D)** Observed front type for prepared interfaces vs both $\bar{\tau}_0$ and $\tilde{\sigma}$. Dots: datapoints.




Figure 5: Dynamic vs quasi-static fronts. Left: Macroscopic loading curves. Right: Fraction of pinned springs shown as in Fig.2A. **(A)** Event I restarted. **(B)** Data from a simulation where driving is applied at $h=0$. Gray scale: the original data with no change to V . Color: driving speed is set to $V=0$ during front propagation. After setting $V=0$ we only show color when at least 5% of a block's springs are slipping.

Supporting information for
Slow slip is a mechanism for slow fronts in the rupture of
frictional interfaces
J. K. Trømborg, H. A. Sveinsson, J. Scheibert, K. Thøgersen, D. S. Amundsen, A. Malthe-Sørenssen

Supporting Table S1: Model parameters. Parameters above the horizontal line are used in the same way as in Ref. (13).

Name	Symbol	Value
Slider length (x)	L	140 mm
Slider height (z)	H	75 mm
Slider width (y)	B	6 mm
Number of blocks	N_x	57
	N_z	31
Slider mass	M	75.6 g
Block mass	m	$M/(N_x N_z)$
Young's modulus	E	3 GPa
Bulk spring modulus	k	$3BE/4$
Bulk spring length	l	$L/(N_x - 1) = H/(N_z - 1)$
Damping coefficient	η	$\sqrt{0.1km}$
Normal load	F_N	1920 N
Elastic foundation modulus	k_f	$k/2$
Driving spring modulus	K	4 MN/m
Driving height	h	5 mm
Driving speed	V	0.4 mm/s
Threshold force coefficient	$\mu_s = f_{\text{thres}}/f_N$	0.4
Slipping force coefficient	$\mu_d = f_{\text{slip}}/f_N$	0.17
Number of interface springs per block	N_s	100
Interface spring stiffness	k_{ij}	$\sqrt{39.2 \text{ GN/m}^2 f_{N,ij}}$
Slipping time mean	$\bar{t}_R$	2 ms
Slipping time standard deviation	δt_R	0.6 ms
Triggering region width	x_{trigger}	22.5 mm
Triggering region prestress	$\bar{\tau}_{\text{trigger}}$	0.3
Time step duration	Δt	$2 \cdot 10^{-7}$ s
Extra damping coefficient	α	$\eta/40$

Supporting Methods


This section supplements the model description found in the main text and its Methods section with detailed information on how we initialize the system and apply the boundary conditions. We also provide some additional information on the simplified model.

The slider is initialized with full normal load F_N and no tangential load F_T by gradually applying F_N without allowing springs to break, a technicality required because the normal forces on the springs, f_{Nij} , start at zero and therefore springs, if allowed to, would break under any stretching. We distribute the load F_N uniformly on the top blocks; apart from this we use the same non-frictional boundary conditions as in (13). The unique equilibrium is found through damped relaxation of typical duration 10 ms. After relaxation, we check that no spring is stretched beyond its strength and introduce the driving spring starting from zero applied driving force F_T . Then F_T , which acts on the block on the left side of the slider situated at height h above the interface, through the driving spring, increases as the driving point moves to the right with speed V .


In the simplified model used for Fig. 3D, we disregard the microscopic state by using a single friction spring per block. Taking parameters from the microscopic reference model described in the main text, each block's spring now has a strength $\tau_{\text{thres}} = \mu_s p_i = N_s f_{\text{thres}}$. The stiffness k_i of a block's friction spring equals the combined stiffness of the springs per block in the reference model. The force on block i from its friction spring is $f_{Ti} = k_i(x_{is} - x_i)$, where x_{is} is the attachment point of the spring to the track. Upon breaking, the spring becomes a slipping spring and its behaviour starts to differ from that of the springs in the microscopic model. We impose a slow slip by letting x_{is} move with a velocity $v_{\text{slow slip spring}}$ for a time $t_{\text{slow slip spring}} = \bar{t}_R$. This process competes with the dynamic friction law where the spring trails the block with x_{is} adjusted in every time step to ensure $|f_{Ti}| \leq \mu_d p_i$, so that the spring attachment point moves with the highest of $v_{\text{slow slip spring}}$ and v_{xi} , the speed of the block in the x -direction. When the block motion reverses (v_{xi} changes sign) the spring returns to the pinned state, but x_{is} continues to move at $v_{\text{slow slip spring}}$ until $t_{\text{slow slip spring}}$ after the spring broke.

The systematic studies leading to Fig. 3D and 4D were done with different normal forces and different initialization from the other simulations. The normal force boundary conditions on the top and bottom were exchanged: this simplifies the analysis by setting a constant normal force $p_i = F_N/N_x$ on all blocks i at the interface. To maintain stability against global rotation, the top blocks interacted with an elastic ceiling with the same properties as the elastic foundation used in Ref. (13) and the other simulations presented here.


To obtain an initial state with a prescribed interfacial shear stress profile we turned the interface springs off during the initialisation. In their place we added to each bottom block the force corresponding to the shear stress to be prescribed. We also introduced the driving spring, but let $V = 0$. During relaxation, the sample moved along the x -axis until the force in the driving spring balanced the net force from the interfacial shear stress. To get rid of oscillations more efficiently we added damping forces $-\alpha(\vec{v}_i)$ on the blocks' motion. After relaxation, the extra forces and the extra damping were turned off and the interfacial springs were introduced, with their attachment points x_{ij} chosen such that the net force on each block was unchanged and the desired distribution of spring forces, $\phi(f_T)$, appeared. We then waited a few timesteps to ensure that the transition from pre- to post-relaxation involved no force discontinuities. Next, instead of driving the system with $V \neq 0$ until rupture was triggered, we started fronts by depinning simultaneously all springs for all blocks to the left of x_{trigger} . The shear stress in the triggering region has a strong influence on the rupture fronts; in order to compare results between simulations we used a constant value $\bar{\tau}_{\text{trigger}}$.



Supporting Figure S1: A fast-slow event arising spontaneously in a simulation using the simplified friction law with a single interface spring per block. The parameter $v_{\text{slow slip spring}} = 1.5$ mm/s (Supporting Methods). (A) Spatio-temporal plot of the instantaneous friction to normal force ratio. (B) Rupture front speed v_c . Block rupture is defined to occur when the interface spring depins. Front speed is measured as in Fig. 2.




Supporting Figure S2: Spatial distributions of prestress τ_0/p for prepared states of the interface. In the front triggering region on the left, the prestress is $\bar{\tau}_0 = \left(\frac{\tau_0}{p} - \frac{f_{\text{slip}}}{f_N} \right) / \left(\frac{f_{\text{thres}}}{f_N} - \frac{f_{\text{slip}}}{f_N} \right) = 0.3$ for all prepared states used in Fig. 3D, 4C and 4D. In the front propagation region the prestress is homogeneous along the interface, at a value varied between prepared states, here $\bar{\tau}_0 = 0.2$ (black) and $\bar{\tau}_0 = 0.3$ (blue). After initialization, all springs in the triggering region are depinned simultaneously. Initiating the events in this way, rather than by driving the system until rupture is triggered, ensures that the force drop / energy release in the triggering region remains the same between simulations.




Supporting Figure S3: Microscopic force distributions significantly affect rupture fronts. The data in Fig. 4A,B repeated with spring force distributions shown in detail. (A) Event II shown as in Fig. 2. (B) Simulation behind A restarted at 1.054 s with a wider distribution $\phi(f_T)$ of shear forces results in a fast-only event. Insets: For each block along the interface, a color coded histogram of $\phi(f_T)$ at 1.054 s. The vertical axis shows the force level in individual springs, which extends up to f_{thres} . The level f_{thres} is shown by the upper white line; it is different for each block because it varies with normal force. The lower white line corresponds to $f_T = 0$ N. The color denotes the fraction of springs found at each value of f_T using an arbitrary bin width. This means that (apart from normalization) each vertical slice in the insets shows the same type of data as Supporting Figure S4A. Offset data: Fraction of slipping springs at 1.054 s.

In order to isolate the effect of $\phi(f_T)$ on front propagation from the influence of front initiation and stress state we leave the loading zone on the left unmodified (it is the same in both insets) so that the restarted event begins like the original; we also let the modified $\phi(f_T)$ have the same mean value as the original $\phi(f_T)$ for all blocks. Thus, the stress state is the same and the only change is in the width of ϕ .



Supporting Figure S4: Dependence of effective static friction coefficient $\mu_s^{\text{eff}} = \tau_{\text{max}}/p$ on the distribution ϕ of forces in the interface springs. **(A)** Uniform and bell-shaped initial distributions of various widths. The bell-shaped distributions are polynomials with roots at $\pm a$ and the functional form $\phi(\xi) = 5/(4a)(1+3|\xi/a|)(1-|\xi/a|)^3$, $\xi \in [-a, a]$. **(B)** Friction to normal force ratio vs block displacement for a block having the spring force distributions in **A** (corresponding colours). Spring relaxation during slip is excluded from the calculation, a valid assumption when the passage of the rupture front is quick compared to the mean slipping time $\langle t_R \rangle$. Markers are located at maxima, which define τ_{max}/p . **(C)** Effective static friction coefficient vs σ , the standard deviation of ϕ . Each marker takes its abscissa from the data in **A** and its ordinate from **B**. Drawn and dashed lines connect markers corresponding to uniform and bell-shaped ϕ , respectively. They are used in Fig. 4C as reference lines for simulation data. For clarity, only a few of the ϕ that were used to determine the lines are shown on this figure.



Supporting Figure S5: Results from an alternative model with a different individual behaviour of the interface springs, showing the robustness of our results against changes in the interfacial law. **(A)** A spontaneously arising fast-slow-fast event, analogous to that in Fig. 2A. **(B)** Observed front type for prepared interfaces, analogous to Fig. 4D.

All data in this figure comes from simulations with a model in which the slipping force f_{slip} decreases linearly with time. This microscopic friction law modifies the slow slip mechanism with respect to the reference microscopic model. Until depinning, the springs have the same behaviour in both models. Upon entering the slipping state, the force from each spring on the block immediately drops to the level $f_{\text{slip}}^0 = \mu_d f_{N,ij}$, as in the reference model. Then the slipping force decays linearly in time with a decay rate depending on the slipping time and the force level at repinning f_{new} ; that is, $f_{\text{slip}} = f_{\text{slip}}^0 - (f_{\text{slip}}^0 - f_{\text{new}})t_s/t_R$, with t_s measured from the time the spring entered the slipping state. The slipping time distribution is the same as in the reference model. The decay in the friction coefficient enables a slow slip motion after the initial rapid slip, which allows this model to sustain slow fronts for a relatively wide range of initial spring stretching configurations and stress states, as seen in **B**.

The parameters used with this model are the same as in the reference model (Supporting Table S1), except for $k_{ij} = \sqrt{54.1 \text{ GN/m}^2 f_{N,ij}}$, $\mu_d = 0.28$ and the new parameter $\mu_{\text{new}} = 0.7\mu_d \approx 0.2$ used to determine $f_{\text{new}} = \mu_{\text{new}} f_{N,ij}$.

Supporting Equations

The data collapse in Fig. 3D is obtained by plotting the slow rupture speed $v_{c,\text{slow}}$ against the quantity $v_{\text{slow slip}} k_i l_0 / (\tau_{\text{thres}} - \tau^0)$, where $v_{\text{slow slip}}$ is the slow slip speed, k_i is the stiffness of the connection between a block and the interface (a single spring in the simplified model and a parallel connection in the reference microscopic model), l_0 is a characteristic length, $\tau_{\text{thres}} = N_s f_{\text{thres}}$ is the maximum shear strength of a block and τ^0 is the shear force in the propagation region before the event is started. In this section we provide a crude argument for this scaling.

When a region of initially homogeneous prestress is being stressed further by block motion on the left, the decaying shear force profile can be written on the form

$$\tau(x) = Af\left(\frac{x-x_0}{l_0}\right) + \tau^0, \quad (1)$$

where A is an amplitude and $f()$ is a function that has magnitude 1 at $x = x_0$ and decays over a characteristic length l_0 that depends on the bulk to interfacial stiffness ratio k/k_i . The function $f()$ is known in 1D (Ref. (29), equation (46)); in 2D it can be measured in an elastostatic model, but its exact form is not required for the present argument.

In a static situation $\tau(x)$ is balanced by the friction forces in the interfacial springs. Ignoring the width of the spring force distribution, the block at x_0 is at its static friction threshold when the force on it from its neighboring blocks is $\tau(x_0) = \tau_{\text{thres}}$, which gives $A = (\tau_{\text{thres}} - \tau^0)$. The next block to the right, at position $x = x_0 + dx$, then has

$$\tau(x_0 + dx) = Af[x_0 + dx] + \tau^0. \quad (2)$$

Here we have used the short-hand notation $f[x] = f((x - x_0)/l_0)$.

As the front tip moves from the block at x_0 to the block at $x_0 + dx$, the force on this block from its neighbours increases to $\tau'(x_0 + dx) = \tau_{\text{thres}}$. It will be useful to rewrite this as $\tau'(x_0 + dx) = \tau_{\text{thres}} = \tau(x_0) = Af[x_0] + \tau^0$. The change in force on the block at $x_0 + dx$ is

$$\Delta\tau(x_0 + dx) = \tau'(x_0 + dx) - \tau(x_0 + dx) \quad (3)$$

$$= A(f[x_0] - f[x_0 + dx]). \quad (4)$$

Assuming a corresponding change in the friction force allows us to relate the force change to a displacement of the block, namely

$$\Delta u(x_0 + dx) = \frac{\Delta\tau(x_0 + dx)}{k_i}. \quad (5)$$

In the next step we will need the displacement of the block at x_0 during the same time interval. As the blocks are at closely spaced points in a deforming elastic medium we will assume $\Delta u(x_0) = \Delta u(x_0 + dx)(1 + O(dx)) \approx \Delta u(x_0 + dx)$.

Now we make the approximation that after breaking, the blocks move at a constant speed $v_{\text{slow slip}}$. It follows that the time it takes from when the block at x_0 breaks and until when the block at $x_0 + dx$ breaks is

$$dt = \frac{\Delta u(x_0)}{v_{\text{slow slip}}}. \quad (6)$$

During this time the front tip has moved the distance dx from one block to the next, and the front speed is

$$v_{c,\text{slow}} = \frac{dx}{dt} = v_{\text{slow slip}} \frac{dx}{\Delta u(x_0)} \quad (7)$$

$$= v_{\text{slow slip}} \frac{k_i}{\tau_{\text{thres}} - \tau^0} \frac{dx}{f[x_0] - f[x_0 + dx]}. \quad (8)$$

Here we recognize an approximation to the spatial derivative of the unknown function $f()$, evaluated at $x = x_0$. We will use the chain rule to separate the non-dimensional and dimensional parts of this derivative, and therefore we define $X(x) = (x - x_0)/l_0$ so that $f[x] = f(X(x))$. With this notation,

$$\frac{df}{dx} = \frac{df}{dX} \frac{dX}{dx} = \frac{df}{dX} \frac{1}{l_0}. \quad (9)$$

We arrive at

$$v_{c,\text{slow}} = v_{\text{slow slip}} \frac{k_i}{\tau_{\text{thres}} - \tau^0} \frac{l_0}{\left(-\frac{df}{dX}\right)_{x=x_0}}. \quad (10)$$

This argument provides a rationale for the linear relationship observed in Fig. 3D, but with the function $f()$ unknown we are not able to predict the value of the coefficient of proportionality. From the shear force profiles we estimate the decay length $l_0 = 7$ mm, a value shared between simulations because we keep k/k_i the same, and rescale $v_{\text{slow slip}}$ with $k_i l_0 / (\tau_{\text{thres}} - \tau^0)$. Note that in the model, $\tau_{\text{thres}} = N_s f_{\text{thres}} = \mu_s p$, with μ_s the threshold force coefficient and p the normal force on the block, which means that the normal force enters in the scaling.